



SPLICE DETAIL: UNITS LARGER THAN A 5252 MAY REQUIRE A STIFFENER ACROSS THE WIDTH. A SHADOW MAY BE VISIBLE FROM BELOW.



NFRC CERTIFIED PERFORMANCE

U-FACTOR TBD
 SHGC TBD
 VT TBD

ORDER #: _____ DATE: _____

PROJECT: _____

LOCATION: _____

CUSTOMER: _____

APPROVED: _____ DATE: _____

MODEL	R.O. OF CURB	QUANTITY
2828	22 1/4" X 22 1/4"	
2852	22 1/4" X 46 1/4"	
3636	30 1/4" X 30 1/4"	
3652	30 1/4" X 46 1/4"	
4242	37" X 37"	
4280	37" X 75"	
5252	46 1/4" X 46 1/4"	
5276	46 1/4" X 69 1/2"	
5296	46 1/4" X 89 1/2"	
5555	48" x 48"	
55102	48" x 96"	
6060	55" X 55"	
6476	57 1/2" X 69 1/2"	
6496	57 1/2" X 89 1/2"	
CUSTOM		

INTERIOR FRAME FINISH: WHITE PVC
 RETAINER FINISH: MILL (STANDARD)
 OTHER _____

CURB WALLS: WHITE INNER / MILL OUTER (STANDARD)
 OTHER: INNER _____
 OUTER _____

GLAZING: OUTER
 ACRYLITE® SATIN SKY2 IR BLOCKING TRANSLUCENT ACRYLIC

INNER
 LUMIRA™ AEROGEL FILLED 10mm MULTIWALL POLYCARBONATE PANEL

Wasco Part of
VELUX® Commercial

VELUX Wells
 85 Spencer Dr, Unit A
 Wells, ME 04090
 1-800-88-VELUX
 veluxusa.com



Skylights pose an inherent risk of injury or death from fall throughs, and the safety of others is of the utmost importance to VELUX. VELUX recommends that the customer, building owner or manager use additional protection with the skylight such as an exterior or interior safety cage, to enhance long-term safety. The building owner or manager is responsible for providing fall protection around the skylight in accordance with OSHA regulations. VELUX also recommends that the building owner or manager restrict roof access only to personnel who have been cautioned as to the location of the skylights, and warned not to sit, step or walk on the skylights.