

GENERAL NOTES:

- 1) UNITS ARE AVAILABLE IN 5:12, 7:12 AND 12:12 PITCHES ONLY.
- 2) MAXIMUM AVAILABLE O.D.CURB WIDTH IS 5'-0".
- 3) SYSTEM DESIGNED FOR 25MM POLYCARBONATE..
- 4) SKYLIGHTS ARE DESIGNED TO SUPPORT A MINIMUM 40 psf POSITIVE LOAD PLUS ALL DEAD LOADS WITH MAXIMUM DEFLECTION OF L/175.
- 5) UNITS ARE SHIPPED ASSEMBLED AND UNGLAZED UNLESS QUOTED OTHERWISE.
- 6) SUPPORTING CURB CONSTRUCTION MUST BE CAPABLE OF SUPPORTING ALL HORIZONTAL AND VERTICAL LOADS IMPOSED BY THE SKYLIGHT ONTO THE CURB.
- 7) INSTALLATION OF SKYLIGHTS IS BY OTHERS.
- 8) OFF-LOADING OF SKYLIGHTS IS THE RESPONSIBILITY OF THE CUSTOMER.

MODEL	OD CURB WIDTH (60" MAX)	OD CURB LENGTH	# BAYS (24" MAX)	PITCH	QUANTITY
CDP				5:12	
CDP				7:12	
CDP				12:12	

25MM GLAZING OPTIONS:

CLEAR	CLEAR IR	CLEAR LUMIRA
OPAL	OPAL IR	

METAL FINISH

MILL	LIGHT BRZ ANODIZED
CLEAR ANODIZE	KYNAR COLOR _____
DARK BRZ ANODIZE	BAKED ENAMEL COLOR _____
MED BRZ ANODIZE	

CLASSIC DOUBLE PITCH 25MM

SALES ORDER #:	
PROJECT NAME:	
LOCATION:	
CUSTOMER:	
WASCO REP:	

NOTE: THESE DRAWINGS AND THE DESIGNS DEPICTED IN THEM, ARE THE PROPERTY OF VELUX AMERICA, LLC. AND CANNOT BE COPIED OR TRANSMITTED IN ANY FORM WITHOUT THE EXPRESS WRITTEN PERMISSION OF SAME.

CUSTOMER VERIFICATION REQUIRED PLEASE INITIAL SUBSEQUENT SHEETS

"REVIEWED" STAMPS ARE NOT ACCEPTED
 UNIT(S) DETAILED ARE AS REQUESTED IN THE BID INVITATION.
 THESE DETAILS ACCURATELY REFLECT THE FIELD DIMENSIONS AND CONDITIONS.
 AND ARE RELEASED FOR FABRICATION.

APPROVED: REJECTED: APPROVED AS NOTED (PER REVIEW BY WASCO):

BY: _____ DATE: _____




DATE: 6/2018

SAFETY CONSIDERATIONS: VELUX SKYLIGHTS ARE DESIGNED TO WITHSTAND NORMAL ELEMENTS OF THE WEATHER. THEY ARE NOT DESIGNED TO WITHSTAND HUMAN IMPACT OR FALLING OBJECTS. THESE SKYLIGHTS SHOULD NOT BE WALKED UPON UNDER ANY CIRCUMSTANCES. THE OWNER OR DESIGNER SHOULD RESTRICT ACCESS ONLY TO AUTHORIZED PERSONNEL WHO HAVE BEEN ADEQUATELY CAUTIONED AS TO THE LOCATION OF THE SKYLIGHT AND INFORMED OF THE WARNING ABOVE OR SAID OWNER SHOULD PROVIDE PROTECTIVE GUARDRAILS OR SCREENS AROUND THE SKYLIGHT.




VELUX Wells
 85 Spencer Dr, Unit A
 Wells, ME 04090
 1-800-88-VELUX
 veluxusa.com





5
2 MULLION @ VERTICAL END
SCALE: 6"=1'-0



1
2 SILL SECTION
SCALE: 6" = 1'


S.S. FASTENERS WILL BE REQUIRED IF PENETRATING PRESSURE TREATED WOOD

1/4" S.S. ANCHORS - MIN. IN ALL PRE-DRILLED HOLES (BY INSTALLER)

CONTINUOUS MASTIC COMPATIBLE WITH ROOFING (BY INSTALLER)

1/4" MIN S.S. OR GALV ANCHORS (BY INSTALLER) IN ALL PRE-DRILLED HOLES

CONTINUOUS MASTIC COMPATIBLE WITH ROOFING MATERIAL (BY INSTALLER)



4
2 VERTICAL END SECTION
SCALE: 6" = 1'

GENERAL CURB/NAILER NOTE: CURBS/NAILERS SHOWN ARE GENERIC. DESIGN AND FABRICATION OF CURBS/NAILERS IS NOT THE RESPONSIBILITY OF WASCO PRODUCTS. THEY MUST BE ADEQUATE TO RESIST ALL VERTICAL AND HORIZONTAL FORCES THAT MAY BE IMPOSED ON THEM BY THE SKYLIGHT SYSTEM.

CLASSIC DOUBLE PITCH 25MM			
CUSTOMER INITIAL			
Wasco Part of		VELUX Wells 85 Spencer Dr, Unit A Wells, ME 04090 1-800-88-VELUX veluxusa.com	
VELUX Commercial			
ORDER#:	INO#	REV 0	SHEET 2 OF 2