



SPlice DETAIL: UNITS LARGER THAN A 5252 MAY REQUIRE A STIFFENER ACROSS THE WIDTH. A SHADOW MAY BE VISIBLE FROM BELOW.



PYRAMID/DOME SHAPE



DOME SHAPE

NFRC CERTIFIED PERFORMANCE

U-FACTOR 0.33
SHGC 0.31
VT 40%



Skylights pose an inherent risk of injury or death from fall throughs, and the safety of others is of the utmost importance to VELUX. VELUX recommends that the customer, building owner or manager use additional protection with the skylight such as an exterior or interior safety cage, to enhance long-term safety. The building owner or manager is responsible for providing fall protection around the skylight in accordance with OSHA regulations. VELUX also recommends that the building owner or manager restrict roof access only to personnel who have been cautioned as to the location of the skylights, and warned not to sit, step or walk on the skylights.

ORDER #: _____ DATE: _____

PROJECT: _____

LOCATION: _____

CUSTOMER: _____

APPROVED: _____ DATE: _____

| MODEL | O.D. OF CURB | QUANTITY |
|-------------|-------------------|----------|
| E3SS2 2828 | 25 1/4" X 25 1/4" | |
| E3SS2 2852 | 25 1/4" X 49 1/4" | |
| E3SS2 3636 | 33 1/4" X 33 1/4" | |
| E3SS2 3652 | 33 1/4" X 49 1/4" | |
| E3SS2 4242 | 40" X 40" | |
| E3SS2 4280 | 40" X 78" | |
| E3SS2 5252 | 49 1/4" X 49 1/4" | |
| E3SS2 5276 | 49 1/4" X 72 1/2" | |
| E3CS2 5296 | 49 1/4" X 92 1/2" | |
| E3SS2 5555 | 51" x 51" | |
| E3SS2 55102 | 51" x 99" | |
| E3SS2 6060 | 58" X 58" | |
| E3SS2 6476 | 60 1/2" X 72 1/2" | |
| E3SS2 6496 | 60 1/2" X 92 1/2" | |
| CUSTOM | | |

FRAME FINISH: PVC: WHITE

RETAINER FINISH: MILL (STANDARD)

OTHER _____

GLAZING:

OUTER

ACRYLITE® SATIN SKY 2 IR BLOCKING
TRANSLUCENT GLAZING

MIDDLE

CLEAR ACRYLIC

INNER

LUMIRA™ AEROGEL FILLED 10mm
MULTIWALL POLYCARBONATE PANEL

E3SS2-NFRC CERTIFIED CURB MOUNT

Wasco Part of
VELUX® Commercial

VELUX Wells
85 Spencer Dr, Unit A
Wells, ME 04090
1-800-88-VELUX
veluxusa.com

DATE:
03/2019

DRAWING NO.:
E3SS2

REV B
SHEET 1 OF 1