



IMPORTANT !!! THIS AREA MUST BE KEPT CLEAR OF ALL FLASHINGS, SEALANTS & ROOFING MATERIALS SO SKYLIGHT WILL WEEP PROPERLY (TYPICAL ALL SIDES)

NFRS CERTIFIED PERFORMANCE	
U-FACTOR	0.66
SHGC	0.45
VT	60%



PYRAMID/DOME

DOME/DOME

ORDER #: _____ DATE: _____

PROJECT: _____

LOCATION: _____

CUSTOMER: _____

APPROVED: _____ DATE: _____

MODEL	R.O. OF CURB	QUANTITY
ESA2 2828	22 1/4" X 22 1/4"	
ESA2 2852	22 1/4" X 46 1/4"	
ESA2 3636	30 1/4" X 30 1/4"	
ESA2 3652	46 1/4" X 69 1/2"	
ESA2 4242	37" X 37"	
ESA2 4280	37" X 75"	
ESA2 5252	46 1/4" X 46 1/4"	
ESA2 5276	46 1/4" X 69 1/2"	
ESA2 5296	46 1/4" X 89 1/2"	
ESA2 5555	48" x 48"	
ESA2 55102	48" x 96"	
ESA2 6060	55" X 55"	
ESA2 6476	57 1/2" X 69 1/2"	
ESA2 6496	57 1/2" X 89 1/2"	
CUSTOM		

INTERIOR FRAME FINISH: WHITE PVC
 RETAINER FINISH: MILL (STANDARD)

OTHER _____

CURB WALLS: WHITE INNER / MILL OUTER (STANDARD)

OTHER: INNER _____
 OUTER _____

GLAZING:

OUTER

ACRYLITE® SATIN SKY 2 IR BLOCKING
 TRANSLUCENT GLAZING

INNER

CLEAR ACRYLIC

Wasco Part of **VELUX® Commercial**

VELUX Wells
 85 Spencer Dr, Unit A
 Wells, ME 04090
 1-800-88-VELUX
 veluxusa.com



Skylights pose an inherent risk of injury or death from fall throughs, and the safety of others is of the utmost importance to VELUX. VELUX recommends that the customer, building owner or manager use additional protection with the skylight such as an exterior or interior safety cage, to enhance long-term safety. The building owner or manager is responsible for providing fall protection around the skylight in accordance with OSHA regulations. VELUX also recommends that the building owner or manager restrict roof access only to personnel who have been cautioned as to the location of the skylights, and warned not to sit, step or walk on the skylights.