



GENERAL NOTES:

- 1) HR UNITS ARE AVAILABLE IN STANDARD WIDTHS (MIN. HR48 WITH 52" O.D. OF CURB) (CUSTOM SIZES ARE AVAILABLE)
- 2) RAFTER SPACING TO BE 4'-0" MAX.
- 3) ALL DOME UNITS MEET OR EXCEED AAMA RECOMMENDATIONS.
- 4) STRUCTURAL RIBS ARE REQUIRED ON HR MODEL -120 THRU -192.
- 5) HEAVY DUTY STRUCTURAL RIBS ARE REQUIRED ON HR MODEL -204 AND UP.
- 6) CENTER PURLINS ARE REQUIRED ON HR MODEL -72 AND UP.
- 7) 45° PURLINS ARE REQUIRED ON HR MODEL 132 AND UP.
- 8) VERTICAL MULLION REQUIRED ON HR MODEL -72 AND UP.
- 9) VERTICAL ENDS WILL BE SHIPPED ASSEMBLED. REMAINDER OF UNIT TO BE SHIPPED KNOCKED DOWN.
- 10) UNIT LENGTH IS NULIMITED.
- 11) (DD) DENOTES DOUBLE DOME.

MODEL	DIM "A"
HRVV-48	52"
HRVV-60	64"
HRVV-72	76"
HRVV-84	88"
HRVV-96	100"
HRVV-108	112"
HRVV-120	124"
HRVV-132	136"
HRVV-144	148"
HRVV-156	160"
HRVV-168	172"
HRVV-180	184"
HRVV-192	196"
HRVV-204	208"
HRVV-216	220"
HRVV-228	232"
HRVV-240	244"



WASCO PRODUCTS, INC.

85 SPENCER DRIVE SUITE A, WELLS, MAINE 04090
(207) 216-4500, FAX (207) 216-4566

HRVV
HALF ROUND
PLAN VIEW

PLN3