



GENERAL NOTES:

- 1) RAFTER LOCATION BASED ON TESTED GLAZING SIZE LIMITATIONS.
- 2) UNIT PITCHES ARE AVAILABLE FROM 3:12 TO 12:12
- 3) GLAZING TO BE PER BELOW WITH NO DEVIATIONS EXCEPT FOR THE ADDITION OF TINT, LOW-E, INERT GAS, ETCHING, OR OTHER GLASS COATINGS AS LONG AS THE SURFACE THAT THESE APPLICATIONS ARE ON ARE NOT IN DIRECT CONTACT WITH THE SURFACE TRANSFERRING THE LOAD TO THE SEALANT.
  - A. INSULATED GLASS (I.G.) UNITS SHALL BE PER TESTED AND APPROVED MAKE-UPS AS FOLLOWS:  $1\frac{5}{16}$ " I.G.:  $\frac{1}{4}$ " TEMPERED,  $\frac{1}{2}$ " AIR SPACE WITH ALUMINUM SPACER OVER  $\frac{1}{4}$ " HEAT STRENGTHENED, .090" SGP INTERLAYER,  $\frac{1}{4}$ " HEAT STRENGTHENED.
  - B. LAMINATED GLASS (L.G.) UNITS SHALL BE PER TESTED AND APPROVED MAKE-UP AS FOLLOWS:  $\frac{9}{16}$ " L.G.:  $\frac{1}{4}$ " HEAT STRENGTHENED, .090" SGP INTERLAYER,  $\frac{1}{4}$ " HEAT STRENGTHENED.



**WASCO PRODUCTS, INC.**

85 SPENCER DRIVE SUITE A, WELLS, MAINE 04090  
(207) 216-4500, FAX (207) 216-4566

**PINNACLE HU  
DOUBLE PITCH (DP)  
PLAN VIEW  
I.G. & L.G.**

**PLN6**