



MODEL	DIM "A"
QRVV-24	26 7/8"
QRVV-30	32 7/8"
QRVV-36	38 7/8"
QRVV-42	44 7/8"
QRVV-48	50 7/8"
QRVV-54	56 7/8"
QRVV-60	62 7/8"
QRVV-72	74 7/8"
QRVV-84	86 7/8"
QRVV-96	98 7/8"
QRVV-108	110 7/8"
QRVV-120	122 7/8"
QRVV-132	134 7/8"
QRVV-144	146 7/8"
QRVV-156	158 7/8"
QRVV-168	170 7/8"

**GENERAL NOTES:**

- 1) QR UNITS ARE AVAILABLE IN STANDARD WIDTHS (MIN QR24 WITH 26 7/8" O.D. OF CURB) (CUSTOM SIZES ARE AVAILABLE)
- 2) RAFTER SPACING TO BE 4'-0" MAX.
- 3) ALL DOME UNITS MEET OR EXCEED AAMA RECOMMENDATIONS.
- 4) STRUCTURAL RIBS ARE REQUIRED ON QR MODEL -72 THRU -96.
- 5) HEAVY DUTY STRUCTURAL RIBS ARE REQUIRED ON QR MODEL -108 AND UP.
- 6) 45° PURLINS ARE REQUIRED ON QR MODEL -72 AND UP.
- 7) VERTICAL ENDS WILL BE SHIPPED ASSEMBLED. REMAINDER OF UNIT TO BE SHIPPED KNOCKED DOWN.
- 8) UNIT LENGTH IS UNLIMITED.
- 9) (DD) DENOTES DOUBLE DOME.



**WASCO PRODUCTS, INC.**

85 SPENCER DRIVE SUITE A, WELLS, MAINE 04090  
(207) 216-4500, FAX (207) 216-4566

QRVV  
QUARTER ROUND  
PLAN VIEW

**PLN4**